

längsnahtgeschweißte Stahlrohre / longitudinally welded steel pipes

Gewichte in kg pro meter / weight in kg per meter

A.D. / O.D. in mm	Wandstärke / Wall Thickness in mm												
	0,8	1,0	1,2	1,5	1,8	2,0	2,5	3,0	3,5	4,0	5,0	6,0	8,0
17,2		0,400	0,474	0,581	0,684	0,750	0,906						
20	0,379	0,469	0,556	0,684	0,808	0,888	1,079						
21,3	0,404	0,501	0,595	0,732	0,866	0,952	1,159	1,354					
22	0,418	0,518	0,616	0,758	0,897	0,986	1,20	1,406					
25	0,477	0,592	0,704	0,869	1,030	1,134	1,387	1,628					
26,9	0,515	0,639	0,761	0,940	1,114	1,228	1,504	1,768					
32	0,616	0,765	0,911	1,128	1,341	1,480	1,819	2,146					
33,7	0,649	0,806	0,962	1,191	1,416	1,564	1,924	2,271	2,607	2,930			
38		0,912	1,089	1,350	1,607	1,776	2,189	2,589					
42,4				1,513	1,802	1,993	2,460	2,915	3,358	3,788			
44,5				1,591	1,895	2,096	2,589	3,070					
45		1,085	1,296	1,609	1,918	2,121	2,620	3,107					
48,3				1,731	2,064	2,284	2,824	3,351	3,867	4,370			
51				1,831	2,184	2,417	2,990	3,551	4,100	4,636			
57		1,381	1,651	2,053	2,450	2,713	3,360	3,995	4,618	5,228			
60,3				2,175	2,597	2,876	3,564	4,239	4,903	5,554			
63,5				2,294	2,739	3,033	3,761	4,476	5,179	5,869			
70				2,534	3,027	3,354	4,162	4,957	5,740	6,511	8,01		
76,1				2,760	3,298	3,655	4,538	5,408	6,266	7,112	8,77		
88,9				3,233	3,866	4,286	5,327	6,355	7,371	8,375	10,35	12,27	
101,6						4,91	6,110	7,29	8,468	9,628	11,91	14,15	
108							6,50	7,77	9,02	10,26	12,70	15,09	
114,3							6,89	8,23	9,56	10,88	13,48	16,03	
120				4,384	5,247	5,820	7,244	8,656	10,056	11,443			
127				4,643	5,558	6,165	7,676	9,174	10,660	12,133			
133							8,05	9,62	11,18	12,73	15,78	18,79	
139,7							8,46	10,11	11,76	13,39	16,61	19,78	
150				5,493	6,579	7,300	9,094	10,876	12,645	14,402			
154				5,641	6,756	7,497	9,341	11,172	12,990	14,797			
159								11,54	13,42	15,29	18,99	22,64	29,79
168,3										16,21	20,14	24,02	
191								13,91	16,18	18,45	22,94	27,37	36,10
193,7										18,71	23,27	27,77	36,64
219,1										21,22	26,40	31,53	41,65
273,1										26,55	33,06	39,52	52,30
323,9										31,56	39,32	47,04	62,32

andere Abmessungen auf Anfrage

other dimensions on request

Qualitäten / qualities:

EN 10217-1
EN 10219

EN 10305-3

DIN 1615
DIN 1626
DIN 2394
DIN 2458

API 5L

ASTM A53

Güten / grades:

P235TR1 / P235TR2
S235JRH / S275J0H / S275J2H /
S355J0H / S355J2H
E235

St 33
St 37.0 / St 44.0 / St 52.0

B / X42 / X46 / X52

A / B